





ESSENS LVT PLUS 2mm (EVP001)

SPECIFICATIONS

DIMENSIONS OVERALL GAUGE

WEAR LAYER

183mm x 915mm

22 planks (39 65sq/ft per box) Colour Shield UV Coating

ESSENS

LVT PLUS 3mm (EVP002)

SPECIFICATIONS

DIMENSIONS OVERALL GAUGE

WEAR LAYER

183mm x 915mm

3mm

16 planks (28 84sq/ft per box) Dynamic Colour Shield UV Coating

ENVIRONMENTAL







PERFORMANCE











Curling after Exposure to Heat

PERFORMANCE

CHARACTERISTICS

Chemical Resistance

Dimensional Squareness

Residual Indentation after

Dimensional Stability &

Castor Resistance

& Straightness

Total Thickness

Static Load

Flexibility

Abrasion Resistance

Specific Gravity

Flammability

Color Fastness to Light

Coefficients of Friction

EN434 94 Shrinkage Rate

Curling EN435 94 (A)

Test Method

EN423.93

EN425.94

EN427.94

EN428 93

EN433.94

Bend around 20mm

Mandrel shows no signs of cracking EN660-1/-2

EN20 ISO105-B02 ASTM D792-91 ASTM D1894-01

Test Result

Pass Class 0

25.000 Cycles. No Visible Damage

Pass

Pass - Accurate to 2mm / 3mm

Pass - No visible indentation

Pass

≤ 0 25% ≤ 2mm

Pass

Pass - 0 1% loss

Pass - Greater Than Level 6

Pass - Density Intact

Pass - Values Within Limits

Pass - Rate of Flame Spread Within Limits

CERTIFICATION & WARRANTIES











DURABILITY





www.essensafloors.com

















All trademarks indicated in this publication are property of their respective owners. Information and specifications contained herein are accurate at the time of printing and may change without notice. All images are for illustration purposes only and colours of actual product may differ from the images contained herein.





