





ESSETS 2mm (ESVOO1)

SPECIFICATIONS

DIMENSIONS **OVERALL GAUGE** PACKAGING

36 planks (54sq/ft per box)

FadeGuard UV Protection

ESSETS 2.5mm (ESV002)

WEAR LAYER

SPECIFICATIONS

DIMENSIONS OVERALL GAUGE

PACKAGING WEAR LAYER

29 planks (43.5sq/ft per box) Double FadeGuard UV Protection

ENVIRONMENTAL







CERTIFICATION & WARRANTIES









PERFORMANCE

CHARACTERISTICS

Chemical Resistance

Castor Resistance

Dimensional Squareness

& Straightness Total Thickness

Residual Indentation after

Static Load

Dimensional Stability &

Curling after Exposure to Heat

Abrasion Resistance

Color Fastness to Light Specific Cravity

Coefficients of Friction

Flammability

Test Method

EN423.93

EN427.94

EN428 93

EN433 94

Shrinkage Rate

Bend around 20mm

Mandrel shows no signs of cracking

EN660-1/-2

EN20 ISO105-B02

ASTM D792-91

ASTM D1894-01

Pass - 0.1% loss

≤ 0.25%

Pass Class 0

25,000 Cycles. No Visible Damage

Pass - Accurate to 2mm / 25mm

Pass - No visible indentation

Pass - Greater Than Level 6

Pass - Density Intact

Pass - Values Within Limits

Pass - Rate of Flame Spread Within Limits

PERFORMANCE

























All trademarks indicated in this publication are property of their respective owners Information and specifications contained herein are accurate at the time of printing and may change without notice. All images are for illustration purposes only and colours of actual product may differ from the images contained herein





