



Nii FLOOR

SPC FLOORING
100 % Virgin Material



Waterproof



Anti-Termite



Scratch Resistant



Abrasion Resistance



Easy to Install



Slip Resistance



Easy to Clean



Comfortable Underfoot

SPECIFICATIONS:

ITEM:	SPC Flooring with click system
DIMENSION:	180mm x 1220mm
TOTAL THICKNESS:	4.0mm
PACKAGING:	10 pcs / 2.1960 m2 per box
SURFACE TEXTURE:	Crystal Smooth
WEAR LAYER:	0.3mm

PERFORMANCE:

CHARACTERISTICS	TEST REQUIREMENTS	TEST METHOD	VERDICT
Size $\leq 305\text{mm}$	$\pm 0.40\text{mm}$	ASTM F2055-17 ISO 24337:2006	Pass as specified
Thickness, product without foam	$\pm 0.13\text{mm}$	ASTM F387-17	Pass
Flatness	for width $\leq 229\text{mm}$	ISO 24337:2006	Pass with minimal tolerance ratio
	f w. concave $\leq 0.15\%$		
	f w. convex $\leq 0.20\%$		
	f l. concave $\leq 0.15\%$		
Openings	for length	ISO 24337:2006	Pass as specified
	f l. convex $\leq 0.20\%$		
Ledging	O ave. $\leq 0.10\text{mm}$	ISO 24337:2006	Pass as specified
	O max. $\leq 0.20\text{mm}$		
Residual Indentation	H ave. $\leq 0.10\text{mm}$	ASTM F1914-17	Pass - No visible indentations
	H max. $\leq 0.15\text{mm}$		
Surface Integrity	Average $\leq 0.18\text{mm}$	ASTM F1914-17	Pass - Structural integrity intact
Dimensional Stability	Residential, (avg, max) $\leq 0.25\%$	ISO 23999:2008 (70°C, 6h)	Pass within tolerance
	Commercial, (max) $\leq 0.20\%$		
Curl	$\leq 0.2\text{mm}$		Pass within tolerance
Resistance to chemicals	No more than a slight change in surface dulling, surface attack or staining	ASTM F925-13	Pass as specified
Resistance to heat	(avg, max) $\Delta E^* < 8$	ASTM F1514-03 (2013)	Pass as specified
Resistance to light	(avg, max) $\Delta E^* < 8$	ASTM F1515-15	Pass with minimal infraction
Static load resistance	For commercial only	ASTM F970-17	Pass - No visible damage

NII HOLDINGS SDN BHD

No. 49, Jalan Utama 1/15, Taman Perindustrian Puchong Utama, 47100 Puchong, Selangor.

Office: +603-8052 0001 | Mobile: +6012-883 2362

Email: sales@niiifloor.com | Website: www.niiifloor.com

Information and specification contained herein are accurate at the time of printing and may change without notice. All images are for illustration purposes only and colours of actual product may differ from the images contained herein.

SCAN ME



ON WEB







S010 Breeze



S219 Light Ash Oak



S432 Chesnut Oak



S089 Ash Oak



S029 Pearl Oak



S209 Tawny Oak



S092 Natural Oak



S140 Prima Oak



S413 Redwood Oak



S466 Walnut Brown



S010 Breeze



S219 Light Ash Oak



S432 Chesnut Oak



S089 Ash Oak



S029 Pearl Oak